

FEATURES

- Used by universities, hospitals and research institutes for long term storing of blood, skincells, DNA and organs
- Digital controller with potential free contact (which makes it possible to connect it to an external alarm)



LAB 11

| LAB | RELIABLE STORING AT LOW TEMPERATURE



LAB 31




LAB 51



DIGITAL CONTROLLER



ALARM BOX



Inner lids (left hand side) which are mandatory for optimized function

	LAB 11	LAB 31	LAB 51
Ambient temperature range	+10 to +30	+10 to +25	+10 to +25
Gross volume, litres	130	300	416
Net volume, litres	130	300	416
Temperature range inside unit	-50 to -86	-50 to -86	-50 to -86
Refrigerant: Mix of Hydro Carbons	Yes	Yes	Yes
Energy consumption / 24 h kwh	5,8	8,5	10
Input power (watt):	480	710	840
DIMENSIONS			
External dimensions (WxDxH)	725x655x865	1305x655x865	1705x655x865
Internal dimensions (WxDxH)	520x450x650	1100x450x650	1500x450x650
Dimension A	725	1305	1705
Dimension B	655	655	655
Dimension C	865	865	865
Dimension D	780	780	780
Dimension E	520	1100	1500
Dimension F	320	900	1300
Dimension G	450	450	450
Dimension H	650	650	650
Dimension J	400	400	400
Dimension L	850	850	850
Insulation, mm	100	100	100
ACCESSORIES			
Basket and dividers	n/a	n/a	n/a
Castors with brakes	Incl.	Incl.	Incl.
Lock	Incl.	Incl.	Incl.
Digital controller w. acoustic alarm	Incl.	Incl.	Incl.
Potential free contact	Incl.	Incl.	Incl.
OTHER DATA			
Outer cabinet	White	White	White
Inner cabinet	Painted steel	Painted steel	Painted steel
Potential free contact	Incl.	Incl.	Incl.
Inner foam lids Incl. (pcs)	2	5	7
Type of cooling	Static	Static	Static
Type of defrost	Manual	Manual	Manual
Power	220 v/ 50 Hz	220 v/ 50 Hz	220 v/ 50 Hz
Power 110 v/ 60 Hz	n/a	n/a	n/a
Thermostat	Digital	Digital	Digital
Net weight, kg	56	80	95
Gross weight, kg	63	88	104
SHIPPING			
20' cont. Capacity	42	24	18
40' cont. Capacity	90	50	56
Standard Trailer capacity	102	60	44